

IAES

International Automotive
Equipment Supply, LLC

Contáctenos:
6917 NW 52nd Street.
Miami - FL 33166
Tel: +1 (305) 468 9400
Fax: +1 (305) 468 9401
eMail: sales@iaesmiami.com

Impact Wrenches

Impact 1/2"

CP7749



BALANCE & POWER

FEATURES

- 1/2" Heavy duty impact wrench
- Twin hammer clutch
- Full power in reverse up to 725 ft-lbs (983Nm)
- Composite handle and magnesium clutch housing
- S2S technology and 3 positive power settings
- Lightweight and low noise level tool

BENEFITS

- Maximize operator comfort with an extremely well balanced tool
- Most convenient and unique reverse technology in the market



S2S Technology is the market's most convenient one handed impact wrench design. The operator can change between forward & reverse with one hand in any position. There is less stress/fatigue on operator's wrist and arm when changing between forward & reverse. It decreases the weight of the tool and improves the overall balance of the tool.

CP7749-2



BALANCE & POWER

FEATURES

- 1/2" Heavy duty impact wrench
- 2" (51mm) extended anvil
- Twin hammer clutch
- Full power in reverse up to 725 ft-lbs (983Nm)
- Composite handle and magnesium clutch housing
- S2S technology and 3 positive power settings
- Lightweight and low noise level tool

BENEFITS

- Maximize operator comfort with an extremely well balanced tool
- Most convenient and unique reverse technology in the market

CP7750



MOST POWERFUL 1/2" IMPACT

FEATURES

- 1/2" Extreme duty impact wrench
- Composite handle and aluminum clutch housing
- Industry best 1,500 bpm, removes even the most stubborn fastener
- 4 position power regulator with 2 speeds in forward and 2 in reverse

BENEFITS

- Control even at high torque levels
- Best in industry to loosen bolts quick and easy

CP7750-2

Same features as CP7750 with 2" (51mm) extended anvil



See accessories on pages 21 & 26



MODEL	PART NUMBER	OUTPUT DRIVE		FREE SPEED		WORKING TORQUE (FW)		MAX TORQUE (REV)		AVERAGE AIR CONS.		AIR CONS. @ LOAD		OVERALL LENGTH		NET WEIGHT		AIR INLET
		in.	mm	rpm	ft-lb	Nm	ft-lb	Nm	cfm	l/s	cfm	l/s	in.	mm	lb	kg	NPTF	
CP7749	894 107 7490	1/2	9,000	75-580	102-786	725	983	4.7	2.2	19	9.0	7.3	186	4.4	1.98	1/4"		
CP7749-2	894 107 7492	1/2	9,000	75-580	102-786	725	983	4.7	2.2	19	9.0	9.3	236	4.7	2.1	1/4"		
CP7750	894 107 7520	1/2	6,400	50-550	68-746	800	1,085	8.0	3.8	32	15.1	7.6	193	5.1	2.3	1/4"		
CP7750-2	894 107 7522	1/2	6,400	50-550	68-746	800	1,085	8.0	3.8	32	15.1	9.6	244	5.6	2.6	1/4"		

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.