

IAES

International Automotive
Equipment Supply, LLC

Contáctenos:

6917 NW 52nd Street.

Miami - FL 33166

Tel: +1 (305) 468 9400

Fax: +1 (305) 468 9401

eMail: sales@iaesmiami.com

ProAlign PA100

Specifications

Models

Mobile Cabinet, Bench Mount and Wall Mount models available.

Cabinet dimensions:

Bench Mount Aligner with 17 in. LCD:
540mm (H) x 584mm (W) x 572mm (D)
21.25 in. (H) x 23 in. (W) x 22.5 in. (D)

Mobile Aligner with 17 in. LCD:
1511mm (H) x 584mm (W) x 572mm (D)
59.5 in. (H) x 23 in. (W) x 22.5 in. (D)

Wall Mount Aligner with 17 in. LCD:
1003mm (H) x 432mm (W) x 495mm (D)
39.5 in. (H) x 17 in. (W) x 19.5 in. (D)

Power Requirements

100-240V, 3.5A-1.75A, 1PH, 50-60Hz

Standard Equipment

Brake Pedal Depressor

Steering Wheel Holder

Options

Hand-held Ride Height Measurement Tool	20-1885-1
Hand-held, Infrared Remote Control	146-55-1
Icon Cordless Remote Indicator ¹	30-421-1-X
Icon Remote Indicator	30-419-1-X
Standard Mechanical Turnplate (2 req.)	25-140-1
Stainless Steel Mechanical Turnplate (2 req.)	25-129-1
Electronic Turnplates (Set of 2)	20-1487-1

PA100 Compatible Sensors

HS400, DSP504, DSP506, DSP506XF, DSP508, DSP508XF



The optional Icon Remote Indicator provides the operator with complete control while making adjustments to the vehicle. Available in conventional or cordless models.

Optional Hand-Held Ride Height Measurement Tool 20-1885-1.



¹Requires XF Pod Kit, 20-2072-1 (standard with DSP506XF or DSP508XF sensors).

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

Intel is the registered trademark of Intel Corporation.



Mobile PA130E system shown with optional 17-inch monitor and optional DSP508XF Cordless Sensors.



"Before" and "after" measurements can be printed to explain service and record work performed. Screens and rear shim templates can also be printed.

Visit our website at www.hunter.com

HUNTER
Engineering Company

11250 Hunter Drive, Bridgeton, MD 63044 U.S.A.
Tel: 1-314-731-3020 • FAX 1-314-731-0132
E-mail: international@hunter.com